DELABIE

Shower kit with thermostatic mixer

Ref. H9741SHYG

Securitouch dual control thermostatic mixer

DESCRIPTION

Shower kit with thermostatic mixer - Ref. H9741SHYG

SECURITHERM dual control thermostatic shower kit with auto-draining device: • Shower mixer with scale-resistant thermostatic cartridge:

Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails. Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge to adjust the temperature.

¹/₄-turn ceramic valve head to adjust the flow rate.

Temperature control from 25 - 41°C.

Double temperature limiter: 1st limiter set at 38°C can be overridden, 2nd limiter set at 41°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water supply.

Flow rate regulated at 9 lpm.

Chrome-plated brass body with ERGO controls.

M1/2" shower outlet.

Filters and non-return valves integrated on the inlets, F3/4".

Mixer with offset standard wall connectors M1/2" M3/4".

• Shower head (ref. 813) and chrome-plated tilting shower head support (ref. 845).

• Anti-stagnation connector FM½" for installation between lower outlet and shower hose, automatically drains the flexible hose and shower head (ref. 880).

Ideal for healthcare facilities, nursing homes, hospitals and clinics. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

Shower kit with thermostatic mixer - Ref. H9741SHYG

Connector	M1/2"	
Technology	SECURITHERM Securitouch thermostatic mixer	
Depth	84mm	
Length	286mm	
Flow rate	9 lpm	
Temperature limiter	Yes	
Finish	Chrome-plated brass	



ADVANTAGES



SECURITHERM: Optimum antiscalding safety




Double maximum temperature limiter



Securitouch thermal insulation prevents burns



Thermostatic: total temperature stability



DELABIE

Norms	ACS	
Warranty	30 MARRANTY	
Repairability		