Auto-draining shower kit with mechanical mixer

Ref. 2539HYG

Mechanical mixer

DESCRIPTION

Auto-draining shower kit with mechanical mixer - Ref. 2539HYG

Mechanical shower kit with auto-draining device:
• Shower mixer with Ø 40mm ceramic cartridge with pre-set maximum temperature limiter.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and sculptured control lever.
M1/2" shower outlet with integrated non-return valve.
Supplied with offset STOP/CHECK connectors, M1/2" M3/4", ideal for hospitals.
• Shower head (ref. 813) with flexible hose (ref. 834T3) and chrome-plated, adjustable, wall-mounted support (ref. 845).
• Auto-draining device FM1/2" for installation between the flexible hose and the shower head, automatically drains the shower head and flexible hose (reduces bacterial development) (ref. 880).
30-year warranty.

ADVANTAGES

- Pre-set maximum temperature limiter
- Handset and flexible hose drain out automatically
- Sculptured control lever for eased grip
- Water saving: flow rate regulated at 9 lpm

TECHNICAL CHARACTERISTICS

Auto-draining shower kit with mechanical mixer - Ref. 2539HYG

Connector	M1/2"
Depth	173mm
Width	175mm
Flow rate	9 lpm
Finish	Chrome-plated brass
Norms	ACS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY