

# Single hole mixer - 100 lpm

Ref. 5612

Mixer with extension column with spout H.650 L.300

## DESCRIPTION

Single hole mixer - 100 lpm - [Ref. 5612](#)

Deck-mounted, single hole mixer for professional kitchens.  
Mixer for professional kitchens with extension column for installation on a stove top.  
Mixer for plunge sinks with swivelling, tubular spout H. 650mm L. 300mm.  
Star-shaped, brass flow straightener with smooth interior.  
Water-free guided valve heads with reinforced mechanisms.  
Shock-resistant, ergonomic ball levers.  
Flow rate 100 lpm at 3 bar.  
Full flow rate within half a turn.  
Chrome-plated brass body and spout.  
Soldered copper pipe water inlets.  
Single hole mixer with reinforced fixings.  
Mixer suitable for intensive use in professional kitchens.  
Mixer for professional kitchens with 30-year warranty.

## TECHNICAL CHARACTERISTICS

Single hole mixer - 100 lpm - [Ref. 5612](#)

|               |                                                                                                                                                                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Height        | 715mm                                                                                                                                                                                                                                                       |
| Drop height   | 650mm                                                                                                                                                                                                                                                       |
| Spout length  | 300mm                                                                                                                                                                                                                                                       |
| Flow rate     | 100 lpm at 3 bar                                                                                                                                                                                                                                            |
| Finish        | Chrome-plated brass                                                                                                                                                                                                                                         |
| Norms         |    |
| Warranty      |                                                                                                                                                                          |
| Repairability |                                                                                                                                                                          |



## ADVANTAGES



Rapid fill: flow rate 100 lpm at 3 bar



Shockproof control levers for intensive use



Brass body and spout suitable for intensive use



Maximum hygiene: spout with smooth interior

