

# Pre-rinse set with mixer

Ref. G6632

With bib tap and swivelling telescopic spout

## DESCRIPTION

Pre-rinse set with mixer - Ref. G6632

Complete pre-rinse set with bib tap.  
Mixer suitable for intensive use in professional kitchens.  
Single hole deck-mounted mixer with:

- valve head with control knobs.
- F3/8" flexible hoses and non-return valves.
- reinforced fixing via 2 threaded rods and back-nuts.

Bib tap with:

- telescopic, swivelling spout L. 200 - 290mm with 20 lpm flow rate at the outlet.
- valve head with control knob.

White hand spray with adjustable jet and 9 lpm flow rate at the outlet (ref. 433000).  
Scale-resistant hand spray and shock-resistant tip.  
White, reinforced, food-grade flexible hose L. 0.95m.  
3/4" stainless steel column.  
Adjustable wall bracket.  
Stainless steel spring guide.  
Pre-rinse set  
30-year warranty.

## TECHNICAL CHARACTERISTICS

Pre-rinse set with mixer - Ref. G6632

|                   |                                                                                                                                                                                                                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector         | F3/8"                                                                                                                                                                                                                                                                                                                                           |
| Height            | 1105 - 1225mm                                                                                                                                                                                                                                                                                                                                   |
| Drop height       | Bib tap: 220mm, hand spray: 460 - 580mm                                                                                                                                                                                                                                                                                                         |
| Flow rate         | 20 lpm with the bib tap; 9 lpm via the hand spray                                                                                                                                                                                                                                                                                               |
| Width to the wall | 35 - 162mm                                                                                                                                                                                                                                                                                                                                      |
| Finish            | Stainless steel                                                                                                                                                                                                                                                                                                                                 |
| Norms             |     |
| Warranty          |                                                                                                                                                                                                                                                              |
| Repairability     |                                                                                                                                                                                                                                                              |



## ADVANTAGES



Rapid fill: full flow rate 20 lpm



Increased resistance: water-free valve heads



Telescopic, swivelling rapid-fill spout



Anti-torsion rotating nuts and PVC sheath

