

# TEMPOMATIC MIX 4

## electronic mixer

Ref. 490006LH

Integrated batteries, stopcocks

### DESCRIPTION

**TEMPOMATIC MIX 4 electronic mixer - Ref. 490006LH**

Deck-mounted electronic basin mixer:  
 Battery-operated with integrated 123 6V Lithium batteries.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Presence detection sensor at the end of the spout optimises detection.  
 Chrome-plated metal body.  
 Cap fixed in place by 2 concealed screws.  
 PEX flexibles with filters and non-return valves.  
 Fixing reinforced by two stainless steel rods.  
 Anti-blocking security.  
 Side temperature control with long lever and adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 4 electronic mixer - Ref. 490006LH**

|               |                                                                                            |
|---------------|--------------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                               |
| Connector     | F3/8"                                                                                      |
| Technology    | Electronic                                                                                 |
| Drop height   | 70mm                                                                                       |
| Spout length  | 105mm                                                                                      |
| Flow rate     | 3 lpm                                                                                      |
| Norms         | ACS  CE |
| Warranty      |         |
| Repairability |         |



### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Batteries integrated into the body of the mixer



Integrated solenoid valve

