

TEMPOMATIC MIX 4 electronic mixer

Ref. 490106LH

Integrated batteries

DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 490106LH

Deck-mounted electronic basin mixer:
Battery-operated with integrated 123 6V Lithium batteries.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Sensor at the end of the spout optimises presence detection.
Chrome-plated stainless steel body.
Cap fixed in place by 2 concealed screws.
PEX flexibles with filters and non-return valves .
Fixing reinforced by two stainless steel rods.
Anti-blocking security.
Side temperature control with long lever and adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490106LH

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS   SVGW 
Warranty	
Repairability	



ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Batteries integrated into the body of the mixer



Integrated solenoid valve

