TEMPOMATIC 4 electronic tap

Ref. 440006

Integrated batteries, stopcock




DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 440006

Deck-mounted electronic basin tap: Battery-operated with integrated 123 6V Lithium batteries. Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener. Duty flush (~60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection. Chrome-plated stainless steel body. Cap fixed in place by 2 concealed screws. PEX flexible with stopcock F3/8" and filter. Fixing reinforced by two stainless steel rods. Anti-blocking security. Suitable for people with reduced mobility. 30-year warranty.

ADVANTAGES



Batteries integrated into the body of the tap



Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap)	- Ref. 440006
------------------------------------	---	---------------

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS 🙆 JWRAS 💹 🔕
Warranty	30 WARRANTY

