TEMPOMATIC 4 electronic tap

Ref. 44000615

Integrated batteries, stopcock Ø 15mm



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 44000615

Deck-mounted electronic basin tap:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body.

Cap fixed in place by two concealed screws.

PEX flexible \emptyset 15mm for compression fittings with stopcock, filter and non-return valve.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Batteries integrated in tap body




Integrated solenoid valve

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 44000615

Supply	6V batteries
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	WRAS Interest Services
Warranty	30 gg warranty
Repairability	50° g



© DELABIE https://www.delabie.com