TEMPOMATIC 4 electronic tap

Ref. 440106

Integrated batteries



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 440106

Deck-mounted electronic basin tap:

Battery-operated with integrated 123 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after the last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body.

Cap fixed in place by 2 concealed screws.

PEX flexibles F3/8" with filter.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Batteries integrated into the body of the tap




Integrated solenoid valve

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 440106

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS VINE SVGW COST C
Warranty	30 gg WARSANTY
Repairability	50 g



© DELABIE https://www.delabie.com