TEMPOMATIC 4 electronic tap

Ref. 440106

Integrated batteries



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 440106

Deck-mounted electronic basin tap:
Battery-operated with integrated 123 6V Lithium batteries.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after the last use).
Presence detection sensor at the end of the spout optimises detection.
Chrome-plated metal body.
Cap fixed in place by 2 concealed screws.
PEX flexibles F3/8" with filter.
Fixing reinforced by two stainless steel rods.
Anti-blocking security.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 90%
- Hygiene: no manual contact
- Batteries integrated into the body of the tap
- Integrated solenoid valve

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 440106

Supply	6V batteries
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS, SVGW, CE, DVGW CERT DIN EN 15091
Warranty	30 YEARS WARRANTY
Repairability	50 YEARS REPAIRABILITY

