

## TEMPOMATIC MIX 4 electronic mixer

Ref. 490000

Recessed mains supply, stopcocks

### DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 490000

Deck-mounted electronic basin mixer:  
230/6V recessed mains supply.  
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Duty flush (~60 seconds every 24 hours after last use).  
Presence detection sensor at the end of the spout optimises detection.  
Chrome-plated stainless steel body.  
Cap fixed in place by 2 concealed screws.  
PEX flexibles with stopcocks F3/8" with stopcocks and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Side temperature control with adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.





### TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490000

Supply	230/6V mains supply (recessed)
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	  
Warranty	
Repairability	



### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Recessed mains supply
-  Anti-bacterial proliferation duty flush

