TEMPOMATIC MIX 4 electronic mixer

Ref. 490000

Recessed mains supply, stopcocks



TEMPOMATIC MIX 4 electronic mixer - Ref. 490000

Deck-mounted electronic basin mixer:

230/6V recessed mains supply.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body.

Cap fixed in place by 2 concealed screws.

PEX flexibles with stopcocks F3/8" with stopcocks and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Side temperature control with adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490000

Supply	230/6V mains supply (recessed)
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	CE ACS
Warranty	30 g
Repairability	50° ERANGANITY



ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Recessed mains supply



Anti-bacterial proliferation duty flush



© DELABIE https://www.delabie.com