

# TEMPOMATIC MIX 4

## electronic mixer

Ref. 490100

Recessed mains supply










### DESCRIPTION

**TEMPOMATIC MIX 4 electronic mixer - Ref. 490100**

Deck-mounted electronic basin mixer:  
 230/6V recessed mains supply.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24hr after last use).  
 Sensor at the end of the spout optimises presence detection.  
 Chrome-plated stainless steel body.  
 Cap fixed in place by 2 concealed screws.  
 PEX flexibles F3/8" with filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Side temperature control with standard lever and adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 4 electronic mixer - Ref. 490100**

Supply	230/6V mains supply (recessed)
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	    
Warranty	
Repairability	

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Recessed mains supply



Integrated solenoid valve

