

# TEMPOMATIC MIX 4

## electronic mixer

Ref. 490100

Recessed mains supply

### DESCRIPTION







**TEMPOMATIC MIX 4 electronic mixer - Ref. 490100**

Deck-mounted electronic basin mixer:  
 230/6V recessed mains supply.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24hr after last use).  
 Sensor at the end of the spout optimises presence detection.  
 Chrome-plated stainless steel body.  
 Cap fixed in place by 2 concealed screws.  
 PEX flexibles F3/8" with filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Side temperature control with standard lever and adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS





**TEMPOMATIC MIX 4 electronic mixer - Ref. 490100**

|              |                                |
|--------------|--------------------------------|
| Supply       | 230/6V mains supply (recessed) |
| Connector    | F3/8"                          |
| Technology   | Electronic                     |
| Drop height  | 70mm                           |
| Spout length | 105mm                          |
| Flow rate    | 3 lpm                          |

|               |   |
|---------------|---|
| Norms         |     |
| Warranty      |    |
| Repairability |    |



### ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Recessed mains supply
-  Integrated solenoid valve

