## TEMPOMATIC MIX 4 electronic mixer

Ref. 490100LH

Recessed mains supply



TEMPOMATIC MIX 4 electronic mixer - Ref. 490100LH

Deck-mounted electronic basin mixer:

230/6V recessed mains supply.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Sensor at the end of the spout optimises presence detection.

Chrome-plated stainless steel body.

Cap fixed in place by 2 concealed screws.

PEX flexibles F3/8" with filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Side temperature control with long lever and adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

## **TECHNICAL CHARACTERISTICS**

TEMPOMATIC MIX 4 electronic mixer - Ref. 490100LH

Supply	230/6V mains supply (recessed)
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	CE ACS ELEAGUA
Warranty	30 g
Repairability	SEPAIRABILITY



## **ADVANTAGES**



Exceptional water savings: 90%



Hygiene: no manual contact



Recessed mains supply



Integrated solenoid valve

