TEMPOMATIC MIX 4 electronic mixer

Ref. 490100LH

Recessed mains supply

DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 490100LH

Deck-mounted electronic basin mixer:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Sensor at the end of the spout optimises presence detection.
Chrome-plated stainless steel body.
Cap fixed in place by 2 concealed screws.
PEX flexibles F3/8" with filters and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with long lever and adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 90%
- Hygiene: no manual contact
- Recessed mains supply
- Integrated solenoid valve

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 490100LH

Supply	230/6V mains supply (recessed)
Connector	F3/8"
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	CE ACS SVGW BELGAQUA
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY