

## TEMPOMATIC 4 electronic tap

Ref. 440101

Plug-in mains supply



### DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 440101

Deck-mounted electronic basin tap:  
230/6V plug-in mains supply.  
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Duty flush (~60 seconds every 24 hours after last use).  
Presence detection sensor at the end of the spout optimises detection.  
Chrome-plated metal body.  
Cap fixed in place by 2 concealed screws.  
PEX flexible F3/8" with filter.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 440101

|              |                             |
|--------------|-----------------------------|
| Supply       | 230/6V plug-in mains supply |
| Connector    | F3/8"                       |
| Technology   | Electronic                  |
| Drop height  | 70mm                        |
| Spout length | 105mm                       |
| Flow rate    | 3 lpm                       |

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Mains supply



Integrated solenoid valve

