

# TEMPOMATIC MIX 3

## electronic mixer

Ref. 492006

Integrated battery, stopcocks



### DESCRIPTION

**TEMPOMATIC MIX 3 electronic mixer** - Ref. 492006

Deck-mounted electronic basin mixer:

Battery-operated with integrated 223 CR-P2 6V Lithium batteries.  
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after the last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

Cap fixed in place by 2 concealed screws, with pictogram to identify sensor easily.

PEX flexibles with stopcocks F3/8", filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Side temperature control lever with adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

### ADVANTAGES



Total hygiene: no manual contact



90% water savings




Battery integrated into the body of the tap



Anti-bacterial proliferation duty flush

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 3 electronic mixer** - Ref. 492006

Supply	6V battery
Connector	F3/8"
Technology	Electronic
Drop height	100mm
Spout length	120mm
Flow rate	3 lpm
Norms	ACS 
Warranty	