

# TEMPOMATIC MIX 3

## electronic mixer

Ref. 49200615

Integrated batteries, Ø 15mm stopcocks





### DESCRIPTION

**TEMPOMATIC MIX 3 electronic mixer** - Ref. 49200615

Deck-mounted electronic basin mixer:  
 Battery-operated with integrated 223 CR-P2 6V Lithium batteries.  
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated solid brass body.  
 Cap fixed in place by two concealed screws, with pictogram to identify sensor easily.  
 PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Side temperature control with adjustable maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 3 electronic mixer** - Ref. 49200615

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	100mm
Spout length	120mm
Flow rate	3 lpm
Norms	
Warranty	

### ADVANTAGES



Batteries integrated in mixer body



90% water savings



Total hygiene: no manual contact



Duty flush limits bacterial proliferation

