TEMPOMATIC 3 electronic tap

Ref. 442006

Integrated battery, stopcock



DESCRIPTION

TEMPOMATIC 3 electronic tap - Ref. 442006

Deck-mounted electronic tap:

Battery-operated with integrated 223 6V Lithium batteries.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

Cap fixed in place by 2 concealed screws, with pictogram to identify the sensor easily

PEX flexible F3/8" with stopcock and filter.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Battery integrated into the body of the tap




Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC 3 electronic tap - Ref. 442006

Supply	6V battery
Connector	F3/8"
Technology	Electronic
Drop height	100mm
Spout length	120mm
Flow rate	3 lpm
Norms	ACS ①
Warranty	30 B



© DELABIE https://www.delabie.com