

# BINOPTIC electronic tap

Ref. 478015

Battery-operated

## DESCRIPTION

**BINOPTIC electronic tap - Ref. 478015**

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
123 6V Lithium battery-operated.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexible with filter and solenoid valve M3/8".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 478015**

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 6V battery                                                                                                                                                                                                                                                                                                                                      |
| Connector     | M3/8"                                                                                                                                                                                                                                                                                                                                           |
| Technology    | Electronic                                                                                                                                                                                                                                                                                                                                      |
| Drop height   | 90mm                                                                                                                                                                                                                                                                                                                                            |
| Spout length  | 125mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |



## ADVANTAGES

-  80% water savings
-  Hygiene: no manual contact
-  6V batteries
-  Anti-bacterial proliferation duty flush

