## **BINOPTIC** electronic tap

Ref. 478015

**Battery-operated** 



## **DESCRIPTION**

BINOPTIC electronic tap - Ref. 478015

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

123 6V Lithium battery-operated.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexible with filter and solenoid valve M3/8".

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).

Suitable for people with reduced mobility.

30-year warranty.

## **ADVANTAGES**



80% water savings



Hygiene: no manual contact



6V batteries




Anti-bacterial proliferation duty

## **TECHNICAL CHARACTERISTICS**

BINOPTIC electronic tap - Ref. 478015

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	90mm
Spout length	125mm
Flow rate	3 lpm
Norms	ACS 😰 CE
Warranty	30g WARRANTY
Repairability	50° REPARABILITY



© DELABIE