

BINOPTIC electronic tap

Ref. 478015

Battery-operated



DESCRIPTION

BINOPTIC electronic tap - Ref. 478015

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
123 6V Lithium battery-operated.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexible with filter and solenoid valve M3/8".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES



80% water savings



Hygiene: no manual contact





6V batteries



Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 478015

| | |
|---------------|---|
| Supply | 6V battery |
| Connector | M3/8" |
| Technology | Electronic |
| Drop height | 90mm |
| Spout length | 125mm |
| Flow rate | 3 lpm |
| Norms |     |
| Warranty |  |
| Repairability |  |

