

## BINOPTIC electronic tap

Ref. 379ENC

Mains supply









### DESCRIPTION

**BINOPTIC electronic tap - Ref. 379ENC**

Recessed electronic basin tap:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Filter and solenoid valve M3/8".  
Chrome-plated brass body.  
Chrome-plated spout for recessed installation.  
Anti-blocking security.  
Spout with smooth interior and low volume of water (limits bacterial niches).  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 379ENC**

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Spout length	200mm
Flow rate	3 lpm
Norms	   
Warranty	
Repairability	

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



LED diagnostic aids



Independent IP65 electronic unit

