TEMPOMATIC MIX 2 electronic mixer

Ref. 494006

Battery-operated

DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 494006

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
Battery-operated with 123 6V Lithium batteries.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated brass body.
PEX flexibles with filters and reduced-stagnation solenoid valves M3/8".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with standard lever and adjustable maximum temperature limiter.
Solenoid valves are upstream of the mixing chamber.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 85%
- Hygiene: no manual contact
- LED diagnostic aid
- Independent IP65 electronic unit

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 2 electronic mixer - Ref. 494006

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	ACS, NF, CE
Warranty	30 YEARS WARRANTY
Repairability	50 YEARS REPAIRABILITY