

TEMPOMATIC MIX 2

electronic mixer

Ref. 494006LH

Battery-operated







DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 494006LH





Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
123 6V Lithium battery-operated.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shockproof infrared presence detection sensor.
Chrome-plated solid brass body.
PEX flexibles with filters and reduced-stagnation solenoid valves M3/8".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with long lever and adjustable maximum temperature limiter .
Solenoid valves upstream of the mixing chamber.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 2 electronic mixer - Ref. 494006LH

Supply	6V battery
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	ACS   
Warranty	

ADVANTAGES

-  Independent IP65 electronic control unit
-  85% water savings
-  Total hygiene: no manual contact
-  Anti-bacterial proliferation duty flush

