TEMPOMATIC MIX 2 electronic mixer

Ref. 494000

Electronic mains supply



DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 494000

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).

Shock-resistant infrared presence detection sensor.

Chrome-plated brass body.

PEX flexibles with filters and solenoid valves M3/8".

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Side temperature control with adjustable maximum temperature limiter.

Solenoid valves are upsteream of the mixing chamber.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 85%



Hygiene: no manual contact



LED diagnostic aid




Independent IP65 electronic unit

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 2 electronic mixer - Ref. 494000

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	ACS (E
Warranty	30 gg warranty
Repairability	50° sepanality



© DELABIE https://www.delabie.com