

# TEMPOMATIC MIX 2

## electronic mixer

Ref. 494000

Electronic mains supply



### DESCRIPTION







**TEMPOMATIC MIX 2 electronic mixer - Ref. 494000**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Shock-resistant infrared presence detection sensor.  
Chrome-plated brass body.  
PEX flexibles with filters and solenoid valves M3/8".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Side temperature control with adjustable maximum temperature limiter.  
Solenoid valves are upstream of the mixing chamber.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 2 electronic mixer - Ref. 494000**

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm

Norms	   
Warranty	
Repairability	

### ADVANTAGES



Exceptional water savings: 85%



Hygiene: no manual contact



LED diagnostic aid



Independent IP65 electronic unit

