TEMPOMATIC 2 electronic tap

Ref. 444000

Electronic tap with mains supply




DESCRIPTION

TEMPOMATIC 2 electronic tap - Ref. 444000

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated solid brass body.
PEX flexible with filter and reduced-stagnation solenoid valve M3/8".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 85%
- Hygiene: no manual contact
- Independent IP65 electronic control unit.
- Anti-bacterial proliferation duty flush



TECHNICAL CHARACTERISTICS

TEMPOMATIC 2 electronic tap - Ref. 444000

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	ACS CE
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY