

# TEMPOMATIC 2 electronic tap

Ref. 444000

Electronic tap with mains supply






## DESCRIPTION

TEMPOMATIC 2 electronic tap - Ref. 444000

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Shock-resistant infrared presence detection sensor.  
Chrome-plated solid brass body.  
PEX flexible with filter and reduced-stagnation solenoid valve M3/8".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMATIC 2 electronic tap - Ref. 444000

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	ACS CE  
Warranty	

## ADVANTAGES



Exceptional water savings: 85%



Hygiene: no manual contact



Independent IP65 electronic control unit.



Anti-bacterial proliferation duty flush

