

## TEMPOMATIC 2 electronic tap

Ref. 444000

Electronic tap with mains supply



### DESCRIPTION

TEMPOMATIC 2 electronic tap - Ref. 444000

Deck-mounted electronic basin tap:  
 Independent IP65 electronic control unit.  
 230/12V mains supply with transformer.  
 Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
 Shock-resistant infrared presence detection sensor.  
 Chrome-plated solid brass body.  
 PEX flexible with filter and reduced-stagnation solenoid valve M3/8".  
 Fixing reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC 2 electronic tap - Ref. 444000

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	   
Warranty	
Repairability	

### ADVANTAGES



Exceptional water savings: 85%



Hygiene: no manual contact



Independent IP65 electronic control unit.



Anti-bacterial proliferation duty flush

