TEMPOMATIC Electronic tap

Ref. 441157

Mains supply





DESCRIPTION

TEMPOMATIC Electronic tap - Ref. 441157

Cross wall electronic basin tap:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).

Chrome-plated fixed spout L. 170mm with anti-rotating pin and back-nut.

Plate is flush to wall.

Shockproof infrared presence detection sensor for wall ≤ 155mm

Anti-blocking security.

For walls ≤ 155mm.

Solenoid valve with integrated filter.

Threaded rods can be cut-to-size.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC Electronic tap - Ref. 441157

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Depth	165mm
Spout length	170mm
Flow rate	3 lpm
Norms	ACS (E
Warranty	30 gg WARRANTY
Repairability	563 REPARABULITY

ADVANTAGES



Total hygiene: no manual contact




90% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush



© DELABIE https://www.delabie.com