

TEMPOMATIC Electronic tap

Ref. 441157

Mains supply



DESCRIPTION

TEMPOMATIC Electronic tap - Ref. 441157

Cross wall electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Chrome-plated fixed spout L. 170mm with anti-rotating pin and back-nut.
Plate is flush to wall.
Shockproof infrared presence detection sensor for wall ≤ 155 mm
Anti-blocking security.
For walls ≤ 155 mm.
Solenoid valve with integrated filter.
Threaded rods can be cut-to-size.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC Electronic tap - Ref. 441157

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Depth	165mm
Spout length	170mm
Flow rate	3 lpm
Norms	ACS CE 
Warranty	
Repairability	

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

