TEMPOMIX time flow mixer

Ref. 795000

With stopcocks



DESCRIPTION

TEMPOMIX time flow mixer - Ref. 795000

Deck-mounted single control time flow basin mixer:

Soft-touch operation.

Temperature control and operation via the push-button.

Time flow ~7 seconds.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Chrome-plated brass body.

Ergonomic chrome-plated metal push-button.

PEX flexibles with stopcocks F3/8", filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 85%



Chrome-plated solid brass, reinforced fixings




Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 795000

Connector	F3/8"
Technology	Time flow
Drop height	60mm
Spout length	110mm
Flow rate	3 lpm
Norms	ACS BELGAQUA BELGAQUA CONTROL OF THE CONTROL OF
Warranty	30 gg WASSANTY
Repairability	50° B



© DELABIE https://www.delabie.com