## **TEMPOMIX time flow mixer**

Ref. 795000

With stopcocks



## **ADVANTAGES**



Exceptional water savings: 85%



Chrome-plated solid brass, reinforced fixings



Soft-touch operation

## **DESCRIPTION**

TEMPOMIX time flow mixer - Ref. 795000

Deck-mounted single control time flow basin mixer:

Soft-touch operation.

Temperature control and operation via the push-button.

Time flow ~7 seconds.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Chrome-plated brass body.

Ergonomic chrome-plated metal push-button.

PEX flexibles with stopcocks F3/8", filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Adjustable maximum temperature limiter.


Suitable for people with reduced mobility.

30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 795000

Technology  Time flow  Drop height  60mm  Spout length  110mm  Flow rate  3 lpm  Norms  ACS ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	Connector	F3/8"
Spout length  110mm  Flow rate  3 lpm  Norms  ACS (1) (2) (3) (3) (3) (3) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	Technology	Time flow
Flow rate 3 lpm  Norms ACS (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	Drop height	60mm
Norms ACS (1) (2) (3) (3) (3)	Spout length	110mm
Warranty 30 <sup>§</sup>	Flow rate	3 lpm
	Norms	ACS 📜 🙆 🐠 🖺
	Warranty	30 g



© DELABIE https://www.delabie.com