

# TEMPOSOFT MIX 2 time flow mixer

Ref. 742510LH

Soft-touch operation



## DESCRIPTION

TEMPOSOFT MIX 2 time flow mixer - Ref. 742510LH

Deck-mounted time flow basin mixer:  
Soft-touch operation.  
Time flow ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Tamperproof scale-resistant flow straightener.  
Chrome-plated brass body.  
PEX flexibles F3/8" with filters and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOSOFT MIX 2 time flow mixer - Ref. 742510LH

|               |                                                                                                                                                                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | F3/8"                                                                                                                                                                                                                                                       |
| Technology    | Time flow                                                                                                                                                                                                                                                   |
| Drop height   | 85mm                                                                                                                                                                                                                                                        |
| Spout length  | 100mm                                                                                                                                                                                                                                                       |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                       |
| Norms         |    |
| Warranty      |                                                                                                                                                                          |
| Repairability |                                                                                                                                                                          |

## ADVANTAGES



Exceptional water savings: 85%



Reinforced fixings



Soft-touch operation



Sleek design

