SECURITHERM shower panel

Ref. 792410

Electronic battery-operated thermostatic



DESCRIPTION

SECURITHERM shower panel - Ref. 792410

Electronic thermostatic shower panel:

With concealed inlet via flexibles, M1/2".

SECURITHERM thermostatic mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Battery-operated with 223 6V Lithium battery.

Infrared presence detection. Shower starts when hand is 4cmfrom the sensor.

Shuts off on demand or automatically after ~60 seconds.

Duty flush (~60 seconds every 24 hours after the last use).

Flow rate set at 6 lpm at 3 bar, can be adjusted, rain-effect spray.

Chrome-plated, tamperproof ROUND shower head.

Concealed fixings.

Filters and non-return valves.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: operate without manual contact



Automatic flush anti-bacterial proliferation



Thermostatic temperature regulation




Instant shut-off if cold water supply fails

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792410

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS BEIGADUA



DELABIE

Warranty



© DELABIE https://www.delabie.com