## **SECURITHERM** shower panel

Ref. 792300

Thermostatic time flow



#### **DESCRIPTION**

SECURITHERM shower panel - Ref. 792300

Thermostatic time flow shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation. Top inlet via in-line stopcocks M½".

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Soft-touch operation.

Chrome-plated, tamperproof, scale-resistant fixed, ROUND shower head with automatic flow rate regulation.

Time flow ~30 seconds.

Flow rate 6 lpm at 3 bar.

Concealed fixings.

Filters and non-return valves.

This product is compatible with thermal and chemical shocks in accordance with current guidelines.

Time flow shower panel suitable for people with reduced mobility. 30-year warranty.

## **ADVANTAGES**



Thermostatic control



Instant shut-off if cold water fails



80% water savings

210




Panel made from aluminium and controls from brass

### TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792300

Connector	M½"
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium



ACS







Norms

© DELABIE https://www.delabie.com

# **DELABIE**

Warranty	30 gg WASTANTY
Repairability	50 g

© DELABIE https://www.delabie.com