SECURITHERM shower panel

Ref. 792310

Thermostatic time flow



DESCRIPTION

SECURITHERM shower panel - Ref. 792310

Thermostatic time flow shower panel:

Anodised aluminium shower panel for wall-mouted, exposed installation. Concealed inlet via flexibles $M\frac{1}{2}$ ".

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38° C with 1st limiter set at 38° C and 2nd limiter set at 41° C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Soft-touch operation.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.

Time flow shower valve ~30 seconds.

Flow rate set at 6 lpm at 3 bar.

Concealed fixings.

Filters and non-return valves.

Time flow shower panel suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Themostatic control



Instant shut-off if cold water fails



80% water savings




Aluminium panel, brass controls

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792310

SECORITHERINI SHOWER Parier - Ref. 772310	
Connector	M½"
Technology	Time flow
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS THE STATE OF T



Warranty



© DELABIE https://www.delabie.com