

# SECURITHERM shower panel

Ref. 792390

Thermostatic mechanical dual control






## DESCRIPTION

**SECURITHERM shower panel - Ref. 792390**

Dual control thermostatic shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
Top inlet via in-line stopcocks M $\frac{1}{2}$ ".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.  
Handset with removable flexible via push-fit rapid STOP connector.  
2 non-time flow 1/4-turn valves to control fixed shower head and handset on flexible hose (wall support supplied).  
Concealed fixings.  
Filters and non-return valves.  
Shower panel suitable for people with reduced mobility.  
30-year warranty.





## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792390**

Connector	M1/2"
Technology	Non-time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	   
Warranty	



## ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Aluminium panel, brass controls

