SECURITHERM shower panel

Ref. 792390

Thermostatic mechanical dual control



DESCRIPTION

SECURITHERM shower panel - Ref. 792390

Dual control thermostatic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Top inlet via in-line stopcocks M½".
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
Handset with removable flexible via push-fit rapid STOP connector.
2 non-time flow 1/4-turn valves to control fixed shower head and handset on flexible hose (wall support supplied).
Concealed fixings.
Filters and non-return valves.
Shower panel suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Themostatic control
- Instant shut-off if cold water fails
- Fixed shower head or handset
- Aluminium panel, brass controls

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792390

Connector	M1/2"
Technology	Non-time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	
Warranty	

