## TEMPOMATIC electronic shower valve

Ref. 452150

Electronic



## **DESCRIPTION**

TEMPOMATIC electronic shower valve - Ref. 452150

Cross wall electronic shower valve:

TEMPOMATIC electronic valve for mixed water supply.

For walls ≤ 155mm.

Power supply by electronic unit with solenoid valve ½".

230/12V transformer.

2 operation modes:

- Automatic activation using presence detection.
- Voluntary ON/OFF activation by passing the hand in front of sensor  $\sim$ 10 cm. Duty flush ( $\sim$ 60 seconds every 24 hours after the last use).

Adjustable time flow from 30 to 60 seconds.

Flow rate 20 lpm.

Chrome-plated solid brass.

Wall plate flush to the wall.

Threaded rods can be cut-to-size.

Electronic shower valve suitable for people with reduced mobility.

30-year warranty.

## **TECHNICAL CHARACTERISTICS**

**TEMPOMATIC** electronic shower valve - Ref. 452150

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	20 lpm
Norms	ACS (E)
Warranty	30 g

## **ADVANTAGES**



230/12V




Total hygiene: no manual contact



Anti-bacterial duty flush



2 operation modes



© DELABIE https://www.delabie.com