## TEMPOMIX time flow shower kit

Ref. 790709

Single control time flow



## **DESCRIPTION**

TEMPOMIX time flow shower kit - Ref. 790709

Recessed time flow shower kit:

Stainless steel wall plate 160 x 160mm.

Standard recessing housing.

Recessing depth can be adjusted from 28 to 48mm.

TEMPOMIX  $\frac{3}{4}$ " single control mixer.

Ligature-resistant collar.

Temperature control and operation via the push-button.

Maximum temperature limiter (can be adjusted by the installer).

Time flow ~30 seconds, soft-touch operation.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

M½" connections for copper tubes Ø 14mm.

Integrated non-return valves and filters.

Chrome-plated metal control.

30-year warranty.

This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

## **ADVANTAGES**



80% water savings



Wall recessed installation



Time flow system tested to over 500,000 operations



Soft-touch operation

## TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790709

Connector	1/2"
Technology	Time flow
Height	160mm
Width	160mm
Flow rate	6 lpm
Norms	ACS B
Warranty	30 E



