TEMPOMIX time flow shower kit

Ref. 790709

Single control time flow

DESCRIPTION

TEMPOMIX time flow shower kit - Ref. 790709

Recessed time flow shower kit:
Stainless steel wall plate 160 x 160mm.
Standard recessing housing.
Recessing depth can be adjusted from 28 to 48mm.
TEMPOMIX ¾" single control mixer.
Ligature-resistant collar.
Temperature control and operation via the push-button.
Maximum temperature limiter (can be adjusted by the installer).
Time flow ~30 seconds, soft-touch operation.
Flow rate 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
M½" connections for copper tubes Ø 14mm.
Integrated non-return valves and filters.
Chrome-plated metal control.
30-year warranty.
This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

ADVANTAGES

- 80% water savings
- Wall recessed installation
- Time flow system tested to over 500,000 operations
- Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790709

Connector	½"
Technology	Time flow
Height	160mm
Width	160mm
Flow rate	6 lpm
Norms	ACS
Warranty	30 YEAR WARRANTY