

PREMIX COMFORT Group thermostatic mixing valve

Ref. 731002

For mixed water 32°-42°C



DESCRIPTION

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731002

Group thermostatic mixing valve for mixed water distribution from 32° - 42°C:
Anti-scalding safety.

Regulates temperature variations.

Filters and non-return valves can be accessed from the outside without removing the mechanism.

Thermal shock with no specific lever needed (push-button on the control knob).

Interchangeable cartridge with automotive cell.

High-resistance chrome-plated brass body.

Maximum hot water temperature: 85°C.

Differential hot water / mixed water: 15°C minimum.

Pressure difference at the inlets: 1 bar maximum (0.5 bar recommended).

Minimum pressure / maximum: 1 - 10 bar (1 - 5 bar recommended).

Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).

Mixed water outlet at the top (purple ring).

For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.

Maximum temperature limiter, can be adjusted by the installer.

Reduced risk of scalding by limiting temperature at the point-of-use.

55 lpm - M³/₄".

10-year warranty.

ADVANTAGES



Automatic shut-off if cold water fails



Temperature stability






Accessible filters and non-return valves



Automotive thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731002

| | |
|------------|---|
| Connector | M ³ / ₄ " |
| Technology | Thermostatic |
| Height | 60mm |
| Depth | 18mm |
| Length | 120mm |
| Flow rate | 55 lpm |
| Norms | ACS   |
| Warranty |  |

