

PREMIX COMFORT Group thermostatic mixing valve

Ref. 731002

For mixed water 32°-42°C



DESCRIPTION

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731002

Group thermostatic mixing valve for mixed water distribution from 32° - 42°C:
Anti-scalding safety.

Regulates temperature variations.

Filters and non-return valves can be accessed from the outside without removing the mechanism.

Thermal shock with no specific lever needed (push-button on the control knob).

Interchangeable cartridge with thermo-reactive cell.

High-resistance chrome-plated brass body.

Maximum hot water temperature: 85°C.

Differential hot water / mixed water: 15°C minimum.

Pressure difference at the inlets: 1 bar maximum (0.5 bar recommended).

Minimum pressure / maximum: 1 - 10 bar (1 - 5 bar recommended).

Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).

Mixed water outlet at the top (purple ring).

For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.

Maximum temperature limiter, can be adjusted by the installer.

Reduced risk of scalding by limiting temperature at the point-of-use.

55 lpm - M $\frac{3}{4}$ ".

30-year warranty.

ADVANTAGES



Automatic shut-off if cold water fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731002

Connector	M $\frac{3}{4}$ "
Technology	Thermostatic
Height	60mm
Depth	18mm
Length	120mm
Flow rate	55 lpm
Norms	  
Warranty	
Repairability	

