# PREMIX NANO thermostatic mixing valve

Ref. 732012

For mixed water from 34 - 60°C

## DESCRIPTION

**PREMIX NANO thermostatic mixing valve** - Ref. 732012

Thermostatic mixing valve for mixed water distribution from 34 - 60°C:
For 1 to 2 taps or 1 shower.
Anti-scalding safety: automatic water shut-off in case of hot or cold water supply failure.
Temperature pre-set at 38°C, can be adjusted by the installer from 34 - 60°C.
Non-return valves and filters.
Minimum flow rate for operation: 3 lpm.
Thermal shocks are possible.
Nickel-plated body, inlets F3/8" and outlet M3/8".
30-year warranty.

## ADVANTAGES

- Automatic shut-off if hot or cold water fails
- Temperature stability
- Accessible filters and non-return valves
- Thermo-reactive cell

## TECHNICAL CHARACTERISTICS

**PREMIX NANO thermostatic mixing valve** - Ref. 732012

| | |
|---|---|
| Connector | 3/8" |
| Technology | Thermostatic |
| Height | 70mm |
| Length | 75mm |
| Finish | nickel-plated |
| Norms | ACS, BELGAQUA |
| Warranty | 30 YEAR WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |