

# PREMIX NANO thermostatic mixing valve

Ref. 732012

For mixed water from 34 - 60°C



## DESCRIPTION

**PREMIX NANO thermostatic mixing valve - Ref. 732012**

Thermostatic mixing valve for mixed water distribution from 34 - 60°C:  
For 1 to 2 taps or 1 shower.  
Anti-scalding safety: automatic water shut-off in case of hot or cold water supply failure.  
Temperature pre-set at 38°C, can be adjusted by the installer from 34 - 60°C.  
Non-return valves and filters.  
Minimum flow rate for operation: 3 lpm.  
Thermal shocks are possible.  
Nickel-plated body, inlets F3/8" and outlet M3/8".  
30-year warranty.

## ADVANTAGES



Automatic shut-off if hot or cold water fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

## TECHNICAL CHARACTERISTICS

**PREMIX NANO thermostatic mixing valve - Ref. 732012**

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | 3/8"                                                                                                                                                                                                                                                                                                                                            |
| Technology    | Thermostatic                                                                                                                                                                                                                                                                                                                                    |
| Height        | 70mm                                                                                                                                                                                                                                                                                                                                            |
| Length        | 75mm                                                                                                                                                                                                                                                                                                                                            |
| Finish        | nickel-plated                                                                                                                                                                                                                                                                                                                                   |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |

