PREMIX NANO thermostatic mixing valve

Ref. 732216

For mixed water from 34 - 60°C

DESCRIPTION

PREMIX NANO thermostatic mixing valve - Ref. 732216

Thermostatic mixing valve for mixed water distribution from 34 - 60°C:
For 1 to 2 taps or 1 shower.
Anti-scalding safety: automatic water shut-off in case of hot or cold water supply failure.
Temperature pre-set at 38°C, can be adjusted by the installer from 34 - 60°C.
Non-return valves and filters.
Minimum flow rate for operation: 3 lpm.
Thermal shocks are possible.
Polished chrome body, hot water inlet F3/8", cold water inlet M3/8"and mixed water outlet M3/8".
30-year warranty.

ADVANTAGES

- Automatic shut-off if hot or cold water fails
- Temperature stability
- Accessible filters and non-return valves
- Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX NANO thermostatic mixing valve - Ref. 732216

Connector	3/8"
Technology	Thermostatic
Height	70mm
Width	75mm
Finish	chrome-plated
Norms	ACS, BELGAQUA, kiwa, IPC
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY