

# PREMIX COMPACT

## Thermostatic mixing valve

Ref. 733015

For mixed water 30 - 60°C



### DESCRIPTION

**PREMIX COMPACT Thermostatic mixing valve - Ref. 733015**

PREMIX COMPACT thermostatic mixing valve for mixed water distribution from 30 - 60°C:

For 1 to 11 points-of-use (depending on the flow rate).

Anti-scalding safety: immediate shut-off if cold water fails.

Anti-cold shower function - automatic shut-off if hot water supply fails.

Adjustable temperature from 30 - 60°C, can be blocked by the installer.

Brass body.

Filters and non-return valves.

Recommended flow rate range: from 5 - 33 lpm.

Thermal shocks are possible.

M $\frac{1}{2}$ ".

40mm centres.

30-year warranty.

### TECHNICAL CHARACTERISTICS

**PREMIX COMPACT Thermostatic mixing valve - Ref. 733015**

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | M $\frac{1}{2}$ "                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Technology    | Thermostatic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Length        | 120mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Finish        | Nickel-plated                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Norms         |       |
| Warranty      |                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Repairability |                                                                                                                                                                                                                                                                                                                                                                                                                                      |

### ADVANTAGES



Automatic flow reduction if cold/hot water fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

